

SRA-750 OB

SEA RIB® ALUMINIUM

OUT-BOARD
ROUND COLLAR

P/N Z99999

STRENGTH & MODULAR

Zodiac Milpro's SEA RIB® ALUMINIUM are built for demanding professional and military users and designed to be strong and reliable.

SRA-750 feature "D-shape" collar technology, increasing the useable deck area, or it can be fitted with a standard round collar. The collar is readily removable to provide easy maintenance.

The SRA-750 aluminium deck integrates deck tracks, allowing rapid re-configuration to suit the mission.

It is fully versatile and capable multi-role boat that is ease in all sea conditions.

CAPACITY

. maximum number of persons (cat. B) :	8	8
. maximum number of persons (cat. C) :	16	16
. maximum payload (cat. B) :	2070 kg	4564 lb
. maximum payload (cat. C) :	2670 kg	5886 lb
. floorboard net area :	8,48 m ²	91,28 ft ²
. flat-floorboard area :	6,36 m ²	68,46 ft ²
. buoyancy tube volume :	5,38 m ³	190 ft ³

DIMENSIONS

. overall length (without engine) :	7,36 m	24' 02"
. inside length :	6,23 m	20' 05"
. overall width :	2,76 m	9' 01"
. inside width :	1,64 m	5' 05"
. overall height (without engine) :	1,65 m	5' 05"
. weight empty :	978 kg	2156 lb
. buoyancy tube diameter :	0,56 m	22"
. hull storage dimensions :	6,51 x 2,20 x 1,21 m ³	21' 4" x 7' 3" x 3' 12"

ENGINE POWER

. shaft length :	single	XL, 635 mm	25"
	twin	L, 508 mm	20"
. recommended power :	single	225 hp	168 kW
	twin	2 x 115 hp	2 x 86 kW
. max. power :	single	250 hp	186 kW
	twin	2 x 150 hp	2 x 112 kW
. max. engine weight :	single	294 kg	648 lb
	twin	2 x 222 kg	2 x 489 lb

SAFETY

. airtight compartments on main tube :	5
. tube inflation pressure :	240 mbar 3,4 PSI
. design categories (ISO 6185 – EC 94-25) :	B and C
. electric bilge pump, ignition protected :	1



BUOYANCY TUBE CONSTRUCTION

. method :	removable slide on collar with bolt rope
. fabric :	1670 dtx, polyester, CSM / neoprene
. fabric color :	grey or black or orange
. intercommunication / inflation valves on tube (delrin) :	4
. all around rubbing strake, flat profile, black :	2
. additional bow rubbing strake horizontal, black :	2

HULL CONSTRUCTION

. material :	marine grade aluminium alloy
. reinforcements :	keel
. airtight compartments :	2
. self-bailers, large flow, with rubber flaps :	2
. hull drain :	1
. transom well :	1
. underdeck fuel tank cavity :	1
. removable deck maintenance panels :	1
. access hatches :	2

LAYOUT

. integrated bow box and anchor locker :	1
. integrated aft storage locker (in transom well) :	1
. deck tracks for modular deck configuration :	6

HANDLING

. exterior lifeline, laced on 53 mm stainless steel D-rings :	1+1
---	-----

OPTIONAL EQUIPMENT

. Rapid Access Door (RAD)
. rigid lifting frame
. lifting sling
. V towing bridle bow
. V towing bridle aft
. stand-up console
. shock mitigation seat
. jockey seat
. jockey seat handle
. foot straps
. bolster
. roll-bar
. self righting system
. rope guard

FUEL SYSTEM

. built-in integrated fuel tank :	250 L	66 USG
. fuel sensor and gauge :		1
. fuel fill and vent, on bow box :		1
. fuel shut off valve, 2 ways :		2

OPTIONAL EXTRA FUEL SYSTEM

. built-in integrated fuel tank :	250 L	66 USG
. fuel sensor and gauge :		1
. fuel fill and vent, on bow box :		1
. fuel shut off valve, 2 ways :		2

TOWING AND LIFTING

. transom towing points – integrated eyes :	2
. bow mooring point – integrated eye :	1
. transom lifting points – integrated eyes :	2
. bow lifting points – integrated eye :	1
. bow post :	1
. tow post :	1

ACCESSORIES

. foot pump :	1
. repair kit (including pressure indicator) :	1
. paddles (telescopic) :	2

SRA-750 OB